


2835 TUNABLE WHITE STRIP/OUTDOOR/168LED

FEATEURES:

- Low power consumption and high light efficiency
- Pure and even light without glare
- CCT tunable: 2700K/4000K/6000K
- Thick 3oz pure copper PCB for excellent thermal management
- Covered in PVC coating; IP65 waterproof for outdoor use
- Cuttable to satisfy various requirements on strip length
- Flexible enough for different lighting projects (bend diameter:>60mm)
- 50,000+ hour long lifespan



Item Code	LEDs/m	Input Voltage	Watt/m	CCT	CRI	Lm/m	Lm/ft	Lm/w	IP Rate	PCB width
	84	24V	8.4	2700K	90	840	256	100	IP 20	10MM
HLOS-24V-2835-168L-CCT	168	24V	16.8 (max.)	4000K	90	1764	537	105	IP 20	10MM
	84	24V	8.4	6000K	90	924	281	110	IP 20	10MM

OPTICAL PARAMETER

LED Type: SMD2835
 Color Rendering Index: 90
 CCT Range: 2700K~6000K
 Beam Angle: 120°
 Light Efficiency: 100~110Lm/w
 Lumen Output/meter: 840~1764Lm/m(256~537Lm/ft)

ELECTRIC PARAMETER

Input Current/m: 0.7A/m (0.2A/ft)
 Input Voltage: DC24V
 Power/M: 16.8W/m (5.1W/ft)
 Static Electricity: 1000V (ESD)
 Size of Section: 100mm (3.94")
 LEDs/Meter: 168LEDs/m
 LEDs of Section: 12 LEDs

